

Clarity 5E TracJack, T568A/B, 180 degree, fog white - OR-TJ5E00



Clarity 5E TracJack, ETL verified to TIA Category 5e component specification. Front-loading and front removable. New universal T568A/B wiring label and tapered wiring towers simplify termination. Center tuned to Clarity 5E patch cords for significant performance above Category 5e



FEATURES

- **ETL Verified to Category 5e component standard:** Ensures standards compliance.
- **Center tuned design:** Transparent interface with Clarity 5e cords.
- **Easy lace IDC housing:** Reduces wiring time
- **Easy to follow universal wiring label:** Quick, user-friendly, eliminates confusion.
- **Front removable:** Less intrusive access for adds, moves, changes.
- **Standard TracJack footprint:** Fits in all Tracjack faceplates and housings.
- **Icon compatible, with 5E Marking on jack face:** Supports 606 designation requirements.
- **RoHS compliant:** Lead free.

Specifications

DIMENSION INFO

Height Metric: 23.37 mm

Ortronics

OR-TJ5E00

Width Metric: 18.54 mm
Depth Metric: 26.92 mm
Height U S: .92"

GENERAL INFO

Category Performance Application: Category 5e/UTP
Color: Fog white
Footprint: TracJack

TECHNICAL INFO

Wire Gauge: 22-26 AWG
Category Rating: Category 5e

CONSTRUCTION INFO

Component2: Array of eight modular dual reactance contacts - Material2: Beryllium copper, Finish_Plating2: Nickel plating and a minimum of 50 micro inches of selective gold plating in contact area
Component3: IDC contacts (Low noise) - Material3: Phosphor bronze, Finish_Plating3: Nickel plating with tin over plate

LISTING AGENCY INFO

ETL 3013270-003
FCC
UL E131600

BUY AMERICAN ACT COMPLIANCE

Country of Origin: MEXICO
Buy American Act Status: Trade Agreement Act Compliant