

Clarity 5E 48-port panel, Cat5e, six-port modules, 19" x 3.5"

OR-PHD5E6U48



Clarity 5E 48-Port High Density Patch Panel is component compliant to EIA/TIA Category 5e performance requirements. It occupies two rack units and measures 19" x 3.5". Jacks are grouped in six-port modules. Part of the Clarity 5E link and channel solution that provides significant installed performance headroom.

features & benefits

- ETL verified to TIA Category 5e component spec: Elevated component performance.
- Center tuned to Clarity 5E patch cords: More transparent mated union.
- Universal wiring: Supports T568A and T568B installs.
- Easy lace 110 termination: Saves installation time.
- Supplied rear cable management: Supports good cabling practice.
- High density design: Maximizes rack utilization.
- RoHS compliant: Lead free.



specifications

General Info

Mod Jack Wiring: Universal T568A/B

Number Of Ports: 48

Listing Agencies/Third Party Information

CUL Listing No: E131600 ETL Listing No: 3013270-004 UL Listing No: E131600

Construction Information

Component1: Panel

Component2: Six-port jack housing Component3: Six-port rear IDC housing

Component4: Array of eight modular dual reactance contacts

Component5: IDC contacts (low noise)

Finish Plating1: Painted black texture with green silkscreen

Finish Plating4: Nickel plating and a minimum of 50 micro inches of selective gold plating in contact area

Finish Plating5: Nickel plating with tin over plate

Material1: .094" Aluminum

Material2: High impact thermoplastic UL 94V-0

Material3: Polycarbonate Material4: Beryllium copper Material5: Phosphor Bronze

Dimensions

Cable Diameter Range: 22-26 AWG

Depth Metric: 3.175 mm Height Metric: 88.9 mm Height U S: 3.5 in Width Metric: 482.6 mm

Technical Information

Category Rating: Category 5e Performance Rating: Category 5e

Buy American Act Compliance

Country of Origin: MEXICO

Buy American Act Status: Trade Agreement Act Compliant