Technical Data Sheet RG6/U Type CATV Coaxial Cable

WEST PENN WIRE



2833 West Chestnut Street Washington, PA 15301 Toll Free: (800) 245-4964 Fax: (724) 222-6420 www.westpenn-wpw.com

PART NUMBER: 841

DESCRIPTION: RG6/U – 1 Conductor 18 AWG Solid, 100% Al. Foil + 65% Al. Braid and an overall PVC Jacket.

NEC RATING: CATV/ CM

APPROVALS: (UL) C(UL) Listed or c(ETL)us Listed

APPLICATION: Indoor for: CATV/MATV

Construction Parameters:

Conductor 18 AWG Bare Copper

Stranding Solid

Insulation Material Gas Injected Polyethylene

Insulation Thickness .180" Nom.

Number of Conductors 1 Center Conductor

Shield 100% Al Foil + 65% Al. Braid

Jacket MaterialPVCOverall Cable Diameter0.245" Nom.Approximate Cable Weight26 Lbs/1M' Nom.Flame RatingArticle 725/800

Floatrical & Environmental Proporties

Electrical & Environmental Properties:	Mhz	db/100ft	
Temperature Rating	-20deg C to 60deg C	5	.45
Max.Capacitance Between Conductors @ 1 KHz	16.2 pf/ft Nom.	55	1.45
Velocity of Propagation	82% Nom.	100	1.85
Impedance	75 ohms Nom.	270	3.07
DC Resistance per Conductor @ 20deg C	6.5 Ohms/1M' Nom.	400	3.85
Jacket Color RoHS Compliant	Black Yes	550	4.62
.ons compilant	103	750	5.40
Mechanical Properties:		1000	6.3
•	06.11	1800	8.85
Max. Recommended Pull Tension	86 lbs.	2250	9.99
Min. Bend Radius (Install)	2.5"	3000	11.9

Connectors and Accessories

F Crimp: CN-56ALM F Compression: CN-F6MCV

Specification Issue Date: 4/12

This document is the property of West Penn Wire. The information contained herein is considered Proprietary and not to be reproduced by any means Without written consent of West Penn Wire Standard Lengths are 1000ft.
The Jacket is sequentially footmarked.
The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.