



Product Information Sheet

UNIVERSAL CABLE RUNWAY

Our most popular cable runway is designed for value conscious customers. The Universal Cable Runway offers the industry standard features you've come to expect. With the runway supported every 5' (1.5 m), maximum load with minimal deflection is 132 lb/ft (59.9 kg).

- Made of 3/8" x 1-1/2" x .065" (9.53 mm x 38 mm x 1.65 mm) wall rectangular steel tubing
- Cross members welded at 12" (300 mm) intervals
- Individually boxed to prevent scratches and damage
- Standard length is 9'-11 1/2"/119.5" (3035 mm)
- Installation Best Practices includes Runway Elevation Kit

Part Number/Color			Width (Dim. A)* in (mm)	Shipping Weight lb (kg)
Gray	White	Black		
10250-104	10250-204	10250-704	4 (100)	18 (8.2)
10250-106	10250-206	10250-706	6 (150)	19 (8.6)
10250-109	10250-209	10250-709	9 (230)	20 (9.1)
10250-112	10250-212	10250-712	12 (300)	25 (11.3)
10250-115	10250-215	10250-715	15 (380)	27 (12.2)
10250-118	10250-218	10250-718	18 (460)	29 (13.2)
10250-124	10250-224	10250-724	24 (610)	32 (14.5)
10250-131	10250-231	10250-731	30 (760)	35 (15.7)
10250-137	10250-237	10250-737	36 (910)	38 (17.2)



Note: Shown in two sections for illustrative purposes, actual product is one piece.

+1-800-834-4969 in U.S. & Canada • www.chatsworth.com



CHATSWORTH PRODUCTS, INC.

©2010 Chatsworth Products, Inc. All rights reserved. CPI, CPI Passive Cooling, MegaFrame, Saf-T-Grip, Seismic Frame, SlimFrame and TeraFrame are federally registered trademarks of Chatsworth Products, Inc. Cube-iT Plus, Evolution, OnTrac, QuadraRack, Simply Efficient and Velocity are trademarks of Chatsworth Products, Inc. All other trademarks belong to their respective companies. 7/10