



NOTES, UNLESS OTHERWISE SPECIFIED:

TOOL WEIGHT: 1.25 lbs./ 0.56 Kg

ALL DIMENSIONS IN METRIC (mm)
[] DIMENSIONS IN INCHES

HANDLES TO SPRING RETURN FREELY
TO OPEN POSITION AFTER CRIMPING

TOOL FRAME MEMBERS AND FASTENERS
TO INCORPORATE BLACK OXIDE FINISH

RECOMMENDED LUBE FOR FRAME LINKAGE:
MOLYKOTE BR2 PLUS
(SUPPLIER DOW CORNING)

ALL GAUGE MARKINGS TO BE OF
EQUAL SIZE OF 1.27[0.05] HEIGHT.

TOOL DIV.
ENGINEERING DEPT.

AUG 02 2006

COPY

R23621BA_TP23621C01_01										
PANDUIT CORP TINLEY PARK, ILLINOIS										
CD•CT-1700										
UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: (.X) ± .01 (.XXX) ± .005 (.XXX) ± .005					UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THREE ANGLE PRACTICE					
01	7-28-06	PWG	WJK	PICTORIAL UPDATE	4212			DRWN BY RYB	MAT'L	SCALE 1:1
00	3-11-98	RYB	SZ	RELEASED	3609		RFL	DATE 3-11-98		DRWG NO. TP23621C01
REV	DATE	BY	CHK	DESCRIPTION	EDN	R	CUST	SUP	GMH	SIZE C