THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



TABLE - 1		
ASSEMBLY PART NUMBER	ITEM DESCRIPTION	WEIGHT
FSCBT3BU-X	OPTICAM 3.0mm CABLE RETENTION BOOT ASSEMBLY WITH BLUE BOOT	3.53g/10 Pcs [.125oz/10 Pcs]
FMCBT3AQ-X	OPTICAM 3.0mm CABLE RETENTION BOOT ASSEMBLY WITH AQUA BOOT	
FMCBT3BL-X	OPTICAM 3.0mm CABLE RETENTION BOOT ASSEMBLY WITH BLACK BOOT	



NOTES:
1. SEE CURRENT CATALOG FOR PART NUMBER SUFFIXES TO INDICATE COLOR AND/OR PACKAGE QUANTITIES.
2. SEE CATALOG FOR ADDITIONAL INFORMATION PERTAINING TO THESE PRODUCTS.
3. 10 ASSEMBLIES PER PACKAGE.
4. MATERIALS:
   A. RETENTION NUT: PLASTIC
   B. BOOT: RUBBER
5. PRIMARY DIMENSIONS ARE METRIC, DIMENSIONS IN BRACKETS ARE CUSTOMARY.

REV	DATE	BY	CHK	DESCRIPTION	ECN - R	CUST	SUP	OTH
1	08-08-06	MC		RELEASED TO PRODUCTION	01799-46			

OPTICAM 3.0mm CABLE RETENTION BOOT ASSEMBLY
CUSTOMER DRAWING

PANDUIT™ CORP.
TINLEY PARK, ILL 60477

THIRD ANGLE PROJECTION

ALL DIMENSIONS ARE GIVEN IN INCHES UNLESS OTHERWISE SPECIFIED.
DIMENSIONAL TOLERANCES ARE:
(.X) (.XXX)±.010 [0.3]
(.XX)±.03 [0.8] ANGLES

DRAWN BY: MC
DATE: 07-31-06
CHK'D: JAW
REVIEW DRAWING NUMBERS

DRAWING FILENAME: M01799AY_DC_3mmX_00A.prt
SCALE: NONE
PART NO.: SEE TABLE 1
DRAWING NO.: 01799-46
SIZE: A