

Sentry Basic CDU

Key Features

- > Power Distribution: 208V Single Phase, 20/30A or 230V 16/32A Power Input.
- > High Density Power Distribution: (24) IEC 60320 C13 outlets
- > Branch Circuit Protection: Sentry CDUs meet UL 60950-1 requirements
- > Vertical Mounting: Zero-U button and bracket mounting options

CB-24V2/VE with C13 Outlets

High Density Power Distribution

The Sentry Basic Cabinet (Power) Distribution Unit (CDU) product family provides a simple solution where reliable power distribution for equipment racks and other data center applications is needed. Basic CDU's provide both power distribution and branch circuit protection.

The Sentry Basic CDU offers different input connections to distribute power from 208V, single phase 20 or 30-Amp input feeds. The Sentry Basic CDU meets the criteria of Branch Circuit Protection by providing overcurrent protection with UL-listed circuit breakers for each branch circuit.


The Sentry Basic Cabinet Power Distribution Unit (CDU) family provides both a reliable and economical solution for your basic power needs.

Additional Benefits:



Branch Circuit Protection

The Sentry CDU Family meets the UL 60950-1 requirement for Branch Circuit Protections
> UL-489 rated circuit breakers



Button Mounting

All CDUs are also compatible with button & "keyhole" style mounting for cabinets. Several cabinet manufacturers are now using this method for installing power distribution units in the cabinet.



Model	Available Input Voltages	Amperage	Available Input Cord	Outlets	Dimensions (L x W x D)*
CB-24V2A401-001	208-240V 50/60Hz	20A	IEC C20 Inlet, Bottom/Frt Entry**	(24) IEC 60320/C13	34.0 x 1.75 x 3.50 in. (862 x 44 x 89 mm)
CB-24V2C401-001	208-240V 50/60Hz	30A	NEMA L6-30P Plug, 10'(3m), Bottom/Frt Cord	(24) IEC 60320/C13	34.0 x 1.75 x 3.50 in. (862 x 44 x 89 mm)
CB-24VEA401-001	230V 50/60Hz	16A	IEC C20 Inlet, Bottom/Frt Entry**	(24) IEC 60320/C13	34.0 x 1.75 x 3.50 in. (862 x 44 x 89 mm)
CB-24VEK401-001	230V 50/60Hz	32A	IEC Blue 2P+G Plug, 10'(3m), Bottom/Frt Cord	(24) IEC 60320/C13	34.0 x 1.75 x 3.50 in. (862 x 44 x 89 mm)

*Product Depth 1.75 in. (44 mm) at the outlets

**Power Cords Sold Separately

Additional Specifications

Agency Approvals

- > US & Canada (cTUVus mark) to UL 60950-1:2003 and CAN/CSA 22.2 No. 60950-1-03
- > European Union (TUVGS Mark) to EN 60950-1:2001
- > FCC Class A, Part 15
- > CE
- > EMC - EN 55022 Class A, EN 55024, CISPR 22 Class A

Branch Circuit Protection

- > Compliant to UL 60950-1

Power Cord Options

- > PTCORD-1 IEC 60320/C19 - NEMA L6-20P , 10ft (3m)
- > PTCORD-2 IEC 60320/C19 - Schuko 10ft (3m)
- > PTCORD-3 IEC 60320/C19 - IEC 60309 (BS4343, CEE17) 16/20A Blue (UK Commando) 10ft (3m)
- > PTCORD-4 IEC 60320/C19 - BS1363 13A (UK) 10ft (3m)



Server Technology

HEADQUARTERS - NORTH AMERICA
 Server Technology, Inc.
 1040 Sandhill Drive
 Reno, NV 89521
 United States
 1.775.284.2000 Tel
 1.775.284.2065 Fax
 sales@servertech.com
 www.servertech.com
 www.servertechblog.com

EMEA
 Server Technology Intl
 Sienna Court
 The Broadway
 Maidenhead
 Berkshire
 SL6 1NJ
 United Kingdom
 +44 (0) 1628 509053 Tel
 +44 (0) 1628 509100 Fax
 salesint@servertech.com

APAC
 Server Technology Intl
 37th Floor, Singapore Land Tower
 50 Raffles Place
 Singapore 048623
 +65 (0) 6829 7008 Tel
 +65 (0) 6234 4574 Fax
 salesint@servertech.com