



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: PS7224-20T

### 24-outlet Vertical Power Strip with 20A Circuit Breaker and 15-ft. Cord with Locking L5-20P Plug

#### Highlights

- 24 outlets
- Convenient and safe covered, on/off switch
- 20-amp circuit breaker
- 15 ft. cord with locking L5-20 input plug
- 72" length



#### Description

Tripp Lite's PS7224-20T power strip offers 20 amp, 120V multi-outlet AC power distribution in a convenient 72 inch mountable housing with NEMA L5-20 locking input plug. Offers horizontal or vertical power distribution in rackmount, raceway and workbench applications. Includes 24 output receptacles with 2.795 inch center-to-center spacing, 15 ft AC line cord and lighted power switch with locking transparent cover to prevent accidental shutoff. Sturdy all-metal extruded aluminum housing stands up to demanding network, laboratory or factory environments.

INPUT/OUTPUT: Input: NEMA L5-20P (twist lock)/Output: 22 NEMA 5-15R & 2 NEMA 5-20R

ELECTRICAL: 120V AC, 50/60Hz, 20A

FORMAT: 72 in. corded, mountable power strip

#### Applications

- Offers vertical or horizontal multi-outlet power distribution in rack enclosures, raceways, desktops and more.

#### Package Includes

- PS7224-20T
- Mounting hardware
- Instruction manual

#### Features

- Sturdy all-metal 72 inch corded strip format with 2.795 inch center-to-center outlet spacing
- Included mounting hardware supports vertical or horizontal mounting in rack enclosures, raceways and more
- Includes 22 NEMA 5-15R and 2 NEMA 5-20R output receptacles
- Includes NEMA L5-20 twist-lock input plug connection
- Ideal for horizontal or vertical raceway style power distribution in office, workbench, industrial, networking and telecom applications
- Lighted power switch with locking transparent cover prevents accidental shutoff
- 20 amp electrical capacity with circuit breaker
- 120V AC, 50/60Hz electrical compatibility

#### Specifications

|                                      |                                                                                                           |
|--------------------------------------|-----------------------------------------------------------------------------------------------------------|
| <b>OUTPUT</b>                        |                                                                                                           |
| Frequency compatibility              | 50 / 60 Hz                                                                                                |
| Output watts                         | 2400                                                                                                      |
| Circuit Breaker (amps)               | 20                                                                                                        |
| Outlet quantity / type               | 2 NEMA 5-15/20R & 22 NEMA 5-15R                                                                           |
| Outlet spacing                       | 2.795 in.                                                                                                 |
| <b>INPUT</b>                         |                                                                                                           |
| Nominal Input Voltage(s) Supported   | 120V AC                                                                                                   |
| Recommended Electrical Service       | 20A 120V                                                                                                  |
| Input connection type                | NEMA L5-20P                                                                                               |
| Input plug features                  | Black                                                                                                     |
| Input cord length (ft.)              | 15                                                                                                        |
| Input cord length (m)                | 4.572                                                                                                     |
| Input cord gauge, type               | 12/3 SJT                                                                                                  |
| Voltage compatibility (VAC)          | 120                                                                                                       |
| <b>LEDS ALARMS &amp; SWITCHES</b>    |                                                                                                           |
| Switches                             | Lighted 2 position switch controls power to all outlets                                                   |
| Locking switch cover                 | Transparent on/off switch cover prevents accidental turn-off                                              |
| <b>PHYSICAL</b>                      |                                                                                                           |
| Unit Dimensions (HWD/in)             | 72 x 1.5 x 1.5                                                                                            |
| Unit Dimensions (HWD/cm)             | 183 x 3.8 x 3.8                                                                                           |
| Unit weight (lbs)                    | 6.6                                                                                                       |
| Unit weight (kg)                     | 2.9964                                                                                                    |
| Material of construction             | Aluminum                                                                                                  |
| Mounting accessories included        | Includes mounting clips                                                                                   |
| Receptacle Color                     | Black                                                                                                     |
| AC line cord color                   | Black                                                                                                     |
| Form factors supported               | Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications |
| Outlets center to center measurement | 72mm                                                                                                      |
| <b>CERTIFICATIONS</b>                |                                                                                                           |
| UL1363 (Power Tap)                   | UL1363                                                                                                    |
| cUL / CSA (Canada)                   | cUL                                                                                                       |
| <b>WARRANTY</b>                      |                                                                                                           |

|                                                |                           |
|------------------------------------------------|---------------------------|
| <b>Product Warranty Period<br/>(Worldwide)</b> | Lifetime limited warranty |
|------------------------------------------------|---------------------------|

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=198](http://www.tripplite.com/en/products/model.cfm?txtModelID=198).

Copyright © 2012 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.