

Tripp Lite 1111 West 35th Street Chicago, IL 60609 USA Telephone: +(773) 869 1234

E-mail: saleshelp@tripplite.com

Model #: RS-1215-RA

1U Rackmount Power Strip with 12 Right-Angle Outlets and 15-ft. Cord



Highlights

- Outlets placed at right angle to accommodate bulky transformers
- 12 widely spaced outlets (6 front / 6 rear)
- Designed for standard 19-in. racks (1U high)
- 15-ft. cord
- 15A circuit breaker

Description

Tripp Lite's RS-1215-RA Power Strip offers 15A capacity AC power distribution in a versatile multi-mount cabinet. Detachable mounting flanges are configurable for rackmount, wallmount and under-counter installation. Uses only 1 rack space (1U) when installed in any 19-in. rack meeting EIA standards. Unfiltered electrical pass-through makes RS-1215-RA ideal for distributing alternate waveform UPS or generator power in rack enclosures, network closets and more. Features 12 NEMA5-15R outlets (6 front/6 rear) placed at a right angle (with ground pin at bottom), 15-ft. AC power cord and lighted power switch with cover that prevents risk of accidental turn-off.

PLUG/OUTLETS: Input: NEMA 5-15P

Output: 12 x NEMA 5-15R (6 front/6 rear)

ELECTRICAL: 120V AC, 50/60Hz, 20A (Requires NEMA 5-15R wall receptacle)

FORMAT: 19-in. rackmount (uses 1 rack space/1U), wallmount, under-counter and more

Applications

• Offers multiple outlet power distribution for multiple loads in 19-in. rackmount, wallmount and under-counter applications such as internetworking, PC systems, telecommunications, audio/video, security, sound reinforcement and more. Ideal for distribution of UPS-, generator- or commercially derived AC power to protected equipment.

Package Includes

- RS-1215-RA 1U Rackmount Power Strip
- Instruction manual with warranty information

Features

- Versatile all-metal cabinet with detachable mounting flanges allows rackmount, wallmount, undercounter and other creative mounting options
- Uses one rack space (1U) in standard 19-in. rack ("zero U" mounting possible in many racks)
- Unfiltered electrical pass-through reliably distributes alternate waveform AC power from UPS or generator to supported equipment
- 12 x NEMA5-15R output receptacles (6 front/6 rear)
- 15-ft. AC cord with NEMA5-15P plug

- Right-angle outlet orientation with ground pin at the bottom
- Lighted power switch confirms power on/off status
- Snap-in switch guard prevents accidental turn off
- 15A electrical capacity with circuit breaker
- 120V AC, 50/60Hz electrical compatibility

Specifications

| OUTPUT | |
|---------------------------------------|--|
| Frequency compatibility | 50 / 60 Hz |
| Circuit Breaker (amps) | 15 |
| Outlet quantity / type | 12 NEMA 5-15R |
| Outlet orientation | 6 front-facing / 6 rear-facing, all with ground pin oriented to the bottom (when viewed in 1U rackmount configuration) |
| INPUT | |
| Nominal Input Voltage(s) Supported | 120V AC |
| Recommended Electrical Service | 15A 120V |
| Input connection type | NEMA 5-15P |
| Input cord length (ft.) | 15 |
| Input cord length (m) | 4.572 |
| Voltage compatibility (VAC) | 120 |
| LEDS ALARMS & SWITCHES | |
| Switches | Red illuminated - positon switch controls power to all outlets |
| Locking switch cover | Transparent locking switch cover prevents accidental shutoff |
| PHYSICAL | |
| Unit Dimensions (HWD/in) | 1.75 (1U) x 17.5 x 4.5 |
| Unit Dimensions (HWD/cm) | 4.445 x 44.45 x 11.4 |
| Unit weight (lbs) | 4.6 |
| Unit weight (kg) | 2.09 |
| Material of construction | Sheet metal |
| Receptacle Color | Black |
| AC line cord color | Black |
| Form factors supported | 1U rackmount, wall-mount and undercounter installation supported |
| Outlets center to center measurement | Distance between Front outlets = 51.6mm; Distance between Rear outlets = 71.1mm |
| SPECIAL FEATURES | |
| TVSS grounding | Back panel nut-and-bolt grounding lug |
| CERTIFICATIONS | |
| UL1363 (Power Tap) | UL1363 (UR status) |

| cUL / CSA (Canada) | cUL |
|--|---------------------------|
| WARRANTY | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=203.

Copyright © 2012 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.