


Indoor/Outdoor Cross-Connect Wire

XCW

PRODUCT DESCRIPTION

Indoor/Outdoor Cross-Connect Wire is intended for cross-connecting points in building entrance enclosures at subscriber's premises and/or in Outside Plant (OSP) enclosures. Each insulated conductor is identified by a combination of solid insulation color, except as noted.



SPECIFICATIONS

Conductor	Solid bare copper
Insulation	Semi-rigid PVC
Standards Compliance	UL 444 CSA C22.2 No. 214-08 RoHS-compliant
NRTL Programs	UL, c(UL) Listed CM

PART NUMBERS AND PHYSICAL CHARACTERISTICS

Part Number	Pair Count	AWG (mm)	Wire Color	Individual Nominal Diameter in (mm)	Overall Nominal Diameter in (mm)	Approx. Weight lbs/kft (kg/km)	Standard Length ft (m)	Package
02-111-13	1	22 (0.64)	White/Blue	0.036 (0.9)	0.07 (1.8)	4 (9)	1,000 (305)	Spool
02-102-13	1	22 (0.64)	Yellow/Blue	0.036 (0.9)	0.07 (1.8)	4 (9)	1,000 (305)	Spool
02-E02-13	1	22 (0.64)	Yellow/Blue	0.036 (0.9)	0.07 (1.8)	4 (9)	3,000 (915)	Spool
02-113-13	1	22 (0.64)	White/Red	0.036 (0.9)	0.07 (1.8)	4 (9)	1,000 (305)	Spool
02-114-13	1	22 (0.64)	White/Black	0.036 (0.9)	0.07 (1.8)	4 (9)	1,000 (305)	Spool
02-513-13*	1	22 (0.64)	White/Red	0.036 (0.9)	0.07 (1.8)	4 (9)	1,000 (305)	Spool
02-514-13*	1	22 (0.64)	White/Black	0.036 (0.9)	0.07 (1.8)	4 (9)	1,000 (305)	Spool
02-120-13	2	22 (0.64)	White/Blue, White/Orange	0.036 (0.9)	0.11 (2.8)	9 (20)	1,000 (305)	Spool
02-H12-13	1	22 (0.64)	White/Violet	0.036 (0.9)	0.07 (1.8)	3 (7)	400 (122)	Spool
02-G11-13	1	22 (0.64)	White/Blue	0.036 (0.9)	0.07 (1.8)	3 (7)	400 (122)	Spool
02-G50-13	1	22 (0.64)	White/Orange	0.036 (0.9)	0.07 (1.8)	3 (7)	400 (122)	Spool
02-H13-13	1	22 (0.64)	Red/White	0.036 (0.9)	0.07 (1.8)	3 (7)	400 (122)	Spool
02-G16-13	1	22 (0.64)	Violet/Blue	0.036 (0.9)	0.07 (1.8)	3 (7)	400 (122)	Spool
02-706-13*	1	24 (0.51)	White/Red	0.036 (0.9)	0.07 (1.8)	3 (7)	1,000 (305)	Spool
02-001-13	1	24 (0.51)	White/Blue	0.036 (0.9)	0.07 (1.8)	3 (7)	1,000 (305)	Spool
02-050-13	1	24 (0.51)	White/Orange	0.036 (0.9)	0.07 (1.8)	3 (7)	1,000 (305)	Spool
02-E12-13	1	24 (0.51)	White/Orange	0.036 (0.9)	0.07 (1.8)	3 (7)	1,000 (305)	Spool
02-006-13	1	24 (0.51)	White/Red	0.036 (0.9)	0.07 (1.8)	3 (7)	1,000 (305)	Spool
02-D06-13	1	24 (0.51)	White/Red	0.036 (0.9)	0.07 (1.8)	3 (7)	600 (183)	Spool
02-053-13	1	24 (0.51)	Red/Blue	0.036 (0.9)	0.07 (1.8)	3 (7)	1,000 (305)	Spool
02-004-13	1	24 (0.51)	Red/Green	0.036 (0.9)	0.07 (1.8)	3 (7)	1,000 (305)	Spool
02-005-13	1	24 (0.51)	Red/Slate	0.036 (0.9)	0.07 (1.8)	3 (7)	1,000 (305)	Spool
02-054-13	1	24 (0.51)	Red/Black	0.036 (0.9)	0.07 (1.8)	3 (7)	1,000 (305)	Spool
02-702-13*	1	24 (0.51)	Red/Black	0.036 (0.9)	0.07 (1.8)	3 (7)	1,000 (305)	Spool
02-002-13	1	24 (0.51)	Yellow/Blue	0.036 (0.9)	0.07 (1.8)	3 (7)	1,000 (305)	Spool
02-409-13	1	24 (0.51)	Blue/Black	0.036 (0.9)	0.07 (1.8)	3 (7)	3,000 (915)	Spool
02-401-13	1	24 (0.51)	White/Blue	0.036 (0.9)	0.07 (1.8)	3 (7)	3,000 (915)	Spool
02-450-13	1	24 (0.51)	White/Orange	0.036 (0.9)	0.07 (1.8)	3 (7)	3,000 (915)	Spool
02-051-13	1	24 (0.51)	White/Green	0.036 (0.9)	0.07 (1.8)	3 (7)	1,000 (305)	Spool
02-052-13	1	24 (0.51)	White/Black	0.036 (0.9)	0.07 (1.8)	3 (7)	1,000 (305)	Spool
02-006-13	1	24 (0.51)	White/Red	0.036 (0.9)	0.07 (1.8)	3 (7)	1,000 (305)	Spool
02-D02-13	1	24 (0.51)	Yellow/Blue	0.036 (0.9)	0.07 (1.8)	3 (7)	600 (183)	Spool
11-001-02	1	24 (0.51)	White/Blue	0.036 (0.9)	0.07 (1.8)	3 (7)	1,000 (305)	Spool
11-001-03	1	24 (0.51)	White/Green	0.036 (0.9)	0.07 (1.8)	3 (7)	2,000 (610)	Spool
02-222-13	2	24 (0.51)	White/Blue, White/Orange	0.036 (0.9)	0.10 (2.5)	6 (13)	1,000 (305)	Spool
02-221-13	2	24 (0.51)	Red/Blue, Red/Orange	0.036 (0.9)	0.10 (2.5)	6 (13)	1,000 (305)	Spool
02-224-13	2	24 (0.51)	Yellow/Blue, Yellow/Orange	0.036 (0.9)	0.10 (2.5)	6 (13)	1,000 (305)	Spool
02-223-13	2	24 (0.51)	White/Orange, White/Green	0.036 (0.9)	0.10 (2.5)	6 (13)	1,000 (305)	Spool
02-032-13	3	24 (0.51)	White/Blue, White/Orange, White/Green	0.036 (0.9)	0.12 (3.0)	9 (20)	1,000 (305)	Spool
02-D30-13	3	24 (0.51)	White/Blue, White/Orange, White/Green	0.036 (0.9)	0.12 (3.0)	9 (20)	600 (183)	Spool
02-041-13	4	24 (0.51)	White/Blue, White/Orange, White/Green, White/Brown	0.036 (0.9)	0.15 (3.8)	13 (29)	1,000 (305)	Spool

*Solid color (not band marked)



Rev 5/13 Ed 12.0

All information, content, data, specifications, packaging and part numbers detailed herein are subject to change. For the most up to date information, please visit SuperiorEssex.com

800.551.8948 | 770.657.6000
SuperiorEssex.com

