CAT5-LAN - CATEGORY 5E SOLID-STATE BUILDING ENTRANCE PROTECTOR

ORDERING INFORMATION

ITW Linx Part Number CAT5-LAN

CAT5-LAN-RJ45

Protects high-performance 4-pair CAT 5e Outside Plant Cables as well as CAT 5e UTP cables for LAN/Data applications (16V). Using 110 punchdown In/Out.

Protects high-performance 4-pair CAT 5e Outside Plant Cables as well as CAT 5e UTP cables for LAN/Data applications (16V). Using RJ-45 In/Out.

* Questions about ordering? Please contact us at 1-800-336-LINX / Contact an authorized distributor for pricing * (MOQ: 12)



TECHNICAL SPECIFICATIONS

PRODUCT SPECIFICATIONS:

Description

Agency Approval UL Primary 497 and Isolated Loop	(497B)
Grounding Requirements	
See Technical Reference page 83-84 for additional ground	ing tips.
Recommended Grounding Impedance<0).5 Ohm
Width	4.25"
Height	4.25"
Depth	1.5"
Weight	0.42 lbs
Product Warranty	Lifetime
Connected Equipment WarrantyUp to \$	\$50,000

SIGNAL LINE SURGE PROTECTION: (LAN)

Signal Perfect Circuitry	Yes
Fused	
Performance Rating	CAT 5e
Clamping Level	16V
Response Time	1-5 Nanoseconds
Capacitance	<20pF
Wires Protected	4-pairs
Termination Type	110 Puchdown or RJ-45



- UL listed for Primary (497) and Isolated Loop (497B) applications
- Exceeds TIA/EIA Standards 568 and 758 for CAT 5e performance
- Solid-state protection for fastest response
- Use between buildings in a campus environment as a building entrance protector or in hostile industrial applications as an isolated loop
- Expandable System Protection -SurgeGate Modules can be attached to one another to expand system protection as your system grows
- Lifetime Product Warranty This surge protector shall be free of any defects in design, materials, or workmanship, or ITW Linx will repair or replace the defective product
- \$50,000 Connected Equipment

For up-to-date warranty information, please visit our web site at www.itwlinx.com.





Signal Perfect™



