

WM SERIES



Shown with optional accessories

FEATURES

- 19" EIA 310-D Compliant
- Horseshoe knockouts on the top and bottom of the enclosure allow already configured patch panels to be installed
- 2 pair of #12-24 rails; fully adjustable
- Solid Steel or Plexiglas Doors
- 1, 2, and 3" conduit and horseshoe knockouts on top and bottom of rear section; 1, 2, and 3" on rear section
- Full piano hinge provides added strength for rear section
- Dust Kit available to protect equipment in high dust/industrial areas
- Center swing-out section provides front/rear access to cables
- Reversible cabinet for left or right hand swing-out
- Vented side panels for air flow
- Weight tested to 1/2" of deflection

WM SERIES

PART NO.	DESCRIPTION
GL2418WM	24"H x 21.25"W x 18"D, Usable depth 16", Maximum rail spacing 11.06", 12 RMU, Plexiglas door Weight capacity 150 lbs.*, Shipping wt. 85 lbs.
GL2418WMS	Same as GL2418WM except solid door
GL24WM	24"H x 21.25"W x 24.5"D, Usable depth 22", Maximum rail spacing 17.62", 12 RMU, Plexiglas door Weight capacity 150 lbs.*, Shipping wt. 95 lbs.
GL24WMS	Same as GL24WM except solid door
GL36WM	36"H x 21.25"W x 24.5"D, Usable depth 22", Maximum rail spacing 17.62", 19 RMU, Plexiglas door Weight capacity 250 lbs.*, Shipping wt. 125 lbs.
GL36WMS	Same as GL36WM except solid door
GL48WM	48"H x 21.25"W x 24.5"D, Usable depth 22", Maximum rail spacing 17.62", 25 RMU, Plexiglas door Weight capacity 300 lbs.*, Shipping wt. 160 lbs.
GL48WMS	Same as GL48WM except solid door

*All maximum weight capacities determined at minimal deflection.

ACCESSORIES

PART NO.	DESCRIPTION
7219	6 position Power Strip for 19" mounting; 5-15R receptacle and 5-15P plug
7219-SR14	14 position (6 front/8 back) Power Strip for 19" mounting; 5-15R receptacle and 5-15P plug with surge protector
7206-14	Stationary Shelf, 17.5"W x 14"D, 80 lb. weight capacity (for use with GL2418)
7206-EIA	Stationary Shelf, 17.468"W x 18"D, 80 lb. weight capacity
7206-FR-A18	Stationary Shelf (front/rear mount adjustable), 17.5"W x 18"D, 150 lb. weight capacity
7206-SL	Sliding Shelf, 16.343"W x 17.5"D, 40 lb. weight capacity
CBB-19	Copper Bus Bar for 19" mounting (isolated)
GR102	Grounding Kit for use with WM, WD, WS, and WE Wall Mounts
7217WS	Fan Assembly with Fan Guards and two 75 CFM fans
FFK1	Four Fan Filters
DK2	Dust Resistant Kit; includes 4 cover plates, 4 fan filters and hardware (not for use with GL2418)