

# Installation Instructions

## SNAP-IN FILLER PANEL

### Application

The 34537-Series and 34538-Series Snap-In Filler Panels shown in the table below can be used in any CPI cabinet with rail spacing for standard 19" panel-width equipment and with square holes on the mounting flanges.

\* (Snap-In filler panels do not fit equipment mounting rails with tapped holes rather than square holes on mounting flanges.)

### Snap-In Filler Panels

PART NO.		DESCRIPTION <sup>(1)</sup>	PACKAGE OF
BLACK	GLACIER WHITE		
34537-000	34537-E00	19" W x 1 RMU	1 Each
34538-000	34538-E00	19" W x 2 RMU	1 Each
34537-001	34537-E01	19" W x 1 RMU	6 Each
34538-001	34538-E01	19" W x 2 RMU	6 Each
34537-002	34537-E02	19" W x 1 RMU	50 Each
34538-002	34538-E02	19" W x 2 RMU	50 Each

<sup>(1)</sup> RMU = Rack Mount Unit = U = 1.75 inch (44.45 mm)

### Tools Required


No tools required. Filler panels snap into square holes on both ends.

### Installation and Removal

Press both ends of filler panel into square holes on mounting flanges of equipment mounting rails. Filler panel snaps into place on both ends.

To remove, use handle in recesses toward ends of filler panel to grab and pull both ends straight out.

1 RMU and 2 RMU snap-in filler panels  
installed in equipment mounting rails



CHATS WORTH PRODUCTS, INC.

IIS-734537 Rev. 4 BMO 01/16/2013

800-834-4969 (USA & Canada) • [www.chatsworth.com](http://www.chatsworth.com) • [techsupport@chatsworth.com](mailto:techsupport@chatsworth.com)  
For international phone numbers, see our website or contact CPI Tech Support.

*This drawing contains proprietary and confidential information and is protected by U.S. and international law. Unauthorized reproduction, disclosure or use of the drawing or the information therein is expressly forbidden except as agreed to in writing by Chatsworth Products, Inc.*