





THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.




FRONT VIEW



FRONT ISOMETRIC VIEW



BLANKING PANEL STACKING



RIGHT VIEW

NOTES:

1. TOOL-LESS BLANKING PANEL TO BE USED IN CEA 310-E COMPLIANT 19" RACKS OR CABINETS.
2. BEST IF INSTALLED UNDER THE FOLLOWING CONDITIONS:
- DISTANCE BETWEEN RAILS: 17.72" - 17.88"
- RAIL THICKNESS RANGE: .07" - .12"
3. INSTALL THE BLANKING PANEL BY ALIGNING THE LOCATING PINS WITH MOUNTING HOLES AND PUSHING IT TOWARDS THE MOUNTING RAILS.
4. VERIFY THAT THE PANEL IS CORRECTLY LOCATED IN A ONE RACK UNIT SPACE OF THE RACK OR CABINET. THE BACK FACE OF THE BLANKING PANELS MUST BE TOUCHING THE FACE OF THE RAILS.
5. REMOVE THE BLANKING PANEL FROM THE MOUNTING RAILS BY PULLING FROM THE HANDLES LOCATED ON EACH SIDE OF THE PANEL.
6. BLANKING PANELS CAN BE STACKED AS SHOWN FOR STORAGE.
7. SEE CURRENT PRICE SHEET FOR PART NUMBER SUFFIX DESIGNATION FOR PACKAGING SIZE AND PRODUCT COLOR.

CAD FILENAME/LAYERS		G03634DH_DC_GB3634DH/11A	
PANDUIT CORP. TINLEY PARK, ILLINOIS			
TLBP1R TOOL-LESS 1U BLANKING PANEL FOR ROUND HOLES			
UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: (.X) ± .1 (.XXX) ± .005 (.XX) ± .03 ANGLES ± 1°		UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THIRD ANGLE PROJECTION.	
DRAWN BY CR-MBA	MAT'L; BLACK ABS	SCALE	NONE
DATE 10/27/10		DRAWING NO.	DWG A SIZE
CHK'D KLN		GB3634DH	

11A	10/27/10	CR-MBA	DJW	NEW RELEASE	GB3634DH	11A	KLN				
REV	DATE	BY	CHK	DESCRIPTION	ECN	- R	CUST	SUP	QC		