

MAX® PATCH PANELS

MAX patch panels provide a flexible, high density modular termination solution for the datacenter and telecommunications room. Using the full line of UTP Z-MAX and MAX modules (available separately), the panel can be configured for a variety of multimedia applications. Blank modules can be used to reserve ports for future capacity.

PATENTED

MODULAR PATCHING

Panels can be mounted directly to fit a standard 19 inch relay rack or cabinet

Available in 16-, 24-, 48-, and 72-port configurations

Modules utilize Siemon's colored icons for easy identification and administration

Bold port numbering enables quick and ready identification of outlets

Write-on area provided for panel designation

Multimedia capability — mix and match many different types of connectors

Lightweight, high strength brushed aluminum with black protective finish

Technical Tip!
Use flat MAX modules for patch panel applications



Individual modules snap into place from front or rear of panel for added installation flexibility

Removable designation labels can be laser printed and enable proper circuit identification for each port

Rear cable management bar included for routing horizontal cables to terminations

ORDERING INFORMATION

MAX® Series Patch Panels: Flat

- MX-PNL-1616-port panel, 1 RMS
- MX-PNL-2424-port panel, 1 RMS
- MX-PNL-4848-port panel, 2 RMS
- MX-PNL-7272-port panel, 2 RMS



MAX® Series Patch Panels: Angled

Siemon's MAX series angled patch panels route cables directly into the vertical cable managers eliminating the need for horizontal cable management between panels.

- MX-PNLA-2424-port angled panel, 1 RMS
- MX-PNLA-4848-port angled panel, 2 RMS



Angled MAX panels are not recommended for use with RS3 rack series. Use the RS series racks.
 Note: 1 RMS = 44.5mm (1.75 in.)

S89D Bracket:

The MAX S89D offers an economical solution for smaller applications while allowing for a range of different media using the full line of MAX modules.

- MX-89D-12.....12-port Max panel mounted on an 89D bracket



Labeling Accessories:

- MX-PNL-LBL4**10 sheets of laser printable labels for 16-port MAX panel
- MX-PNL-LBL6**10 sheets of laser printable labels for 24- and 48-port MAX panel

**Visit our web site or contact our Technical Support Department for labeling software.

Reusable Hook and Loop Cable Managers:

- VCM-25-(XXX)-(X)Roll of 25 cable managers
 - VCM-250-(XXX)-(X)Spool of 250 cable managers
- Use (XXX) to specify length:
 06 = 152mm (6 in.), holds 51mm (2 in.) diameter cable bundle
 12 = 305mm (12 in.), holds 102mm (4 in.) diameter cable bundle
 18 = 457mm (18 in.), holds 153mm (6 in.) diameter cable bundle
- Use (X) to specify color: 1 = black, 2 = white, 3 = red, 4 = gray, 5 = yellow, 6 = blue, 7 = green, 9 = orange

For related product information request Spec Sheet(s):

- MAX Modules Tool-less (PROD-SS-MXM)
- MAX 5e Module Punch-down (PROD-SS-MPD)
- MAX 6 Modules (PROD-SS-MX6)

Because we continuously improve our products, Siemon reserves the right to change specifications and availability without prior notice.
 MAX® and TERA® are trademarks of Siemon

North America
 Watertown, CT USA
 Phone (1) 860 945 4200 US
 Phone (1) 888 425 6165 Canada

Europe/Middle East/Africa
 Surrey, England
 Phone (44) 0 1932 571771

Asia/Pacific
 Shanghai, P.R. China
 Phone (86) 21 5385 0303

Latin America
 Bogota, Colombia
 Phone (571) 657 1950