

Building Entrance Terminals

INDOOR - 66 BLOCK SERIES - BET

2625QC/QC

25 PAIR - INDOOR BET - 66/66 - NO COVER

Product Specifications

UL497 Primary Protector for Communication Circuits

NAFTA Country of Origin: CANADA - All Models are "Buy America Act" Approved.

These 16 AWG steel building entrance terminals feature reliable 66 block style Quick Clip connectors for both input and output terminals. Connectors can accept up to an 18 AWG line termination. Also included are multiple external and internal ground lugs. UL Approval standard on all terminals. Standard 5 -pin protector modules, available in gas tube, solid state and hybrid versions, can be purchased separately. Call for more detailed information on RDUP/RUS-listed units.

Features & Benefits

- 16 AWG Powder Coated Steel Construction
- Equipped with an Internal 26 AWG Fuse Link
- External Ground Connectors Accept 6 14 AWG Wire
- Industry Standard 5 Pin Design
- Exceeds UL497 Primary Protection Standards
- 66 Block Accepts 22 26 AWG Wire/18 19 AWG Stripped Solid Copper Wire



2625QC/QC

Ordering Information

Model Number	Stock Code	Pair Count	Input	Output	Dimensions (H" x W" x D")	Weight (lbs)
2625QC/QC	114012	25	66	66	10.00 x 3.50 x 3.25	3

Circa Telecom, Inc ® 2013 - Version 1.03

6914 W. Linebaugh Ave - Tampa, Fl 33625 3 6556 - Eax 813 676 2060 - Email circatech@circatelecom.com - www.circ

Phone 800.783.6556 - Fax 813.676.2060 - Email circatech@circatelecom.com - www.circatelecom.com





Building Entrance Terminals

INDOOR - 66 BLOCK SERIES - BET

2625QC/QC

25 PAIR - INDOOR BET - 66/66 - NO COVER

Physical Dimensions

UL497 Primary Protector for Communication Circuits

10.00 x 3.50 x 3.25 (H" x W" x D")

Underwriters Laboratories

000 00 RING 1 IN TIP 1 OUT 0000 TIP 1 IN er RING 1 OUT 10.00 • 2 LRING 25 OUT TIP 25 IN TIP 25 OUT RING 25 IN ไททิกกิกไ 3.25 0 3.50

Notes

Installation:

Indoor Wall Mount

RUS Approved Material - 2011 Edition RUS Publication 344-2 (Section 4.1.2 and 4.2)

Circa Telecom, Inc ® 2013 - Version 1.03