# **Detailed Specifications & Technical Data**



### ENGLISH MEASUREMENT VERSION

## FF3X03LD Faceplates and Panels - FX ECX Frame



For more Information please call

1-800-Belden1



#### **General Description:**

## FX ECX FRAME, OM3, 3 PORTS, LC DUPLEX, AQUA ADAPTERS

Jsage (Overall)	
Suitable Applications:	FiberExpress Solutions, Backbone, Telecommunications Room, Main Distribution Room, Data Centers
Related Parts:	FX ECX Panels, FX Pigtails, FX Brilliance
Physical Characteristics (Connectivity)	
Capacity	
Max. Capacity:	6 Fibers, 3 LC Duplex Ports
Access	
Front Connection:	Static
Dimensions Dimensions:	
Height (in.) Width (in.) Length (in.)   1.300 6.340 1.390	
Materials Materials:	
Description Type Material Co	lor
Adapter Sleeve Zirconia-Ceramic Front Connector Body LC-Duplex Plastic - UL94V-0 Aq	
Frame Plastic - UL94V-0 Ad	
Weight	
Weight:	0.200 lbs.
Packaging	
Packaging:	Individually packaged in a plastic bag, Shipped in cardboard box (60/box)
Nechanical Characteristics (Connectivity)	
Storage Temperature Range:	-10°C To +75°C
Operating Temperature Range:	-10°C To +60°C
Applicable Specifications and Agency Compli	ance (Overall)
Applicable Standards & Environmental Programs	
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	07/01/2006
MII Order #39 (China RoHS):	EUP 50

## **Detailed Specifications & Technical Data**



#### ENGLISH MEASUREMENT VERSION

### FF3X03LD Faceplates and Panels - FX ECX Frame

Suitability						
Suitability	- Indoor:	Y	es			
Fransmissio	n Characteristics	(Connectivity)				
Notes (Overa	all)					
	· ·					
Notes:		bout this product, please contact our T	echnical Support group (ibdn.ts@	belden.com) or your loc	al sales representative.	
Notes:	additional information a	bout this product, please contact our T	echnical Support group (ibdn.ts@	belden.com) or your loc	al sales representative.	
Notes: For	additional information a	bout this product, please contact our T	iechnical Support group (ibdn.ts@	gbelden.com) or your loc	al sales representative.	

Revision Number: 0 Revision Date: 02-06-2017

## © 2017 Belden, Inc All Rights Reserved.

All Rights Reserved. Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information, and belief at the date of its publication. The information provided in this Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.