

# Inova OnTime<sup>®</sup> 4-Digit Clock Specifications



## **Specifications**

LED Color Options	Red, Green	Plastic Cabinet	
Weight	Aluminum cabinet: 2 lbs (0.9 kg); stainless cabinet: 3.75 lbs (1.7 kg); plastic cabinet: 1.6 lbs (0.7 kg)	Colors	
Cabinet Dimensions	12" L x 6" H x 2.2" D	Black Pantone 426 C	
Display	4" hour and minute numerals	Putty	
Accuracy	+/- approximately 200 milliseconds	Pantone 7500 U	Pantone Gray
Operating Temperature	32º to 104º F (0º to 40º C)	Off-White	2 C
Operating Humidity	95% maximum, non-condensing		
Mounting Options	Surface, Pendant, Cantilever, Flush Inset, Double Sided		
Certifications	UL 1950, ETL Listed, CE Marked, RoHS Compliant		

Note: Specifications and design are subject to change without notice.

#### Features

- Red or green LED seven-segment display
- Visible from over 150 feet (50 meters)
- Set automatically by SNTP (Simple Network Time Protocol)
- 10/100BaseT Ethernet compatible
- DHCP or static IP addressable
- Power over Ethernet (IEEE 802.3af) technology
- No master clock or serial connection required
- Easily upload firmware upgrades
- Service light status indicator

- Two-year limited warranty
- Telnet control for:
  - IP address configuration
  - SNTP server address
  - Time zone offset from UTC, Daylight Saving Time
  - 12/24 hour format time display
  - Status reporting

### Models

Model #	Orientation/Mounting	Cabinet Material	Cabinet Color	# of Digits	LED color
ONT4BK-P	Single-sided	Plastic	Black	4-digit	Red
ONT4PT-P	Single-sided	Plastic	Putty	4-digit	Red
ONT4OW-P	Single-sided	Plastic	Off-white	4-digit	Red
ONT4BK	Single-sided	Aluminum	Black	4-digit	Red
ONT4SS	Single-sided	Stainless Steel	Stainless Steel	4-digit	Red
ONT4FM	Single-sided, flush mount	Plastic case, aluminum face plate	Black	4-digit	Red
ONT4BKFMS	Single-sided, flush mount	Plastic case, stainless face plate	Black and stainless	4-digit	Red
ONT4BK-P-G	Single-sided	Plastic	Black	4-digit	Green
ONT4PT-P-G	Single-sided	Plastic	Putty	4-digit	Green
ONT4OW-P-G	Single-sided	Plastic	Off-white	4-digit	Green
ONT4BK-G	Single-sided	Aluminum	Black	4-digit	Green
ONT4SS-G	Single-sided	Stainless Steel	Stainless Steel	4-digit	Green
ONT4FM-G	Single-sided, flush mount	Plastic case, aluminum face plate	Black	4-digit	Green
ONT4BKFMS-G	Single-sided, flush mount	Plastic case, stainless face plate	Black and stainless	4-digit	Green
ONT4DSBK-P	Double-sided	Plastic	Black	4-digit	Red
ONT4DSPT-P	Double-sided	Plastic	Putty	4-digit	Red
ONT4DSOW-P	Double-sided	Plastic	Off-white	4-digit	Red
ONT4DSBK	Double-sided	Aluminum	Black	4-digit	Red
ONT4DSSS	Double-sided	Stainless Steel	Stainless Steel	4-digit	Red
ONT4DSBK-P-G	Double-sided	Plastic	Black	4-digit	Green
ONT4DSPT-P-G	Double-sided	Plastic	Putty	4-digit	Green
ONT4DSOW-P-G	Double-sided	Plastic	Off-white	4-digit	Green
ONT4DSBK-G	Double-sided	Aluminum	Black	4-digit	Green
ONT4DSSS-G	Double-sided	Stainless Steel	Stainless Steel	4-digit	Green

## Accessories

Model #	Description
ONT4KIT	Ethernet mounting kit, 4-digit
ONT4NEMA	NEMA enclosure for 4-digit clock
722442	Power injector, Ethernet, Phihong



1.800.637.1077 | info@inovasolutions.com | www.inovasolutions.com/network-clocks