

3FT RAPIDRUN® VGA (HD15) FLYING LEAD

2212-60082-003 | [Quiktron](#)


FEATURES & BENEFITS

RapidRun® is designed to be the standard for in-wall audio/video installations. Using pre-terminated Break-away flying leads and wall plates with an in-wall runner ensures flexible, efficient, high quality connections for all types of equipment, with no field terminations.

Electrical Characteristics

3 Coax Conductor:

- Impedance: 75±5Ω
- Capacitance: 71±2pF/ft
- Velocity of propagation: 78±1%
- DC resistance: 237±10Ω/km
- Dielectric strength: 500VAC/1 minute min.
- Insulation resistance (500V): 10MΩ/KM

3 Twisted Pair Conductors

- DC resistance: 93.25Ω/m at 20°C
- Dielectric strength: 750VAC/minute min.
- Insulation resistance: 100MΩ/KM at 20°C

Physical Characteristics

- Voltage rating: 30V
- Temperature rating: 80°C
- Temperature range: -25° - 80°C
- Minimum bend radius: 90mm

Conductor (qty. 3)

- Conductor type: 28AWG (7/0.127) (tinned copper)
- Dielectric: Foam PE
- Shield: Spiral shield (tinned copper) (90% coverage)
- Insulation: PVC

Conductor (qty. 3 twisted pair)

- Conductor type: 24AWG (7/0.2) (tinned copper)
- Foil shield: Aluminum foil (100% coverage)
- Insulation: PVC

Conductor (qty. 2 conductors)

- Conductor type: 24AWG (7/0.2) (tinned copper)
- Insulation: PVC

Overall Cable

- Foil shield: Aluminum foil (100% coverage)
- Braided shield: 24/8/0.12 (tinned copper) (85% coverage)
- Jacket: Matte PVC

VGA Connector (Qty. 1)

- Connector Type - HD15
- Gender - Male
- Contact Material - Brass, 30m Gold Plating
- Insulation - Black PBT

RapidRun Din Connector (Qty. 1)

- Connector Type - DIN 15 pin
- Gender - Male
- Contact Material - Brass, 3µm Gold Plating
- Insulation - Black PBT

SPECIFICATIONS

GENERAL INFO

Color: Black
Product Series: RapidRun
Type: RapidRun Multi-Format Flying Leads