# Product Specifications





## 1375191-5

SL110 Series Modular Jack, 8-position, RJ45, category 5e, T568A/T568B, unshielded, without dust cover,orange

## **Body Features**

110 Block Material

Polycarbonate

#### **Configuration Features**

Keyed	No
Number of Positions	8
Wiring Pattern	Universal

#### **Contact Features**

Contact Base Material	Beryllium copper
Contact Mating Area Plating Material	Gold
Contact Mating Area Plating Thickness	50.00 µin   1.27 µm

#### **Dimensions**

Insulated Conductor Outside Diameter	0.057 in	Ι	1.45 mm
Solid Wire Range	.51 mm²	Ι	. 65 mm²
Stranded Wire Range	.14 mm <sup>2</sup>	Ι	. 2 mm²
Wire Range	22 AWG	Ι	24 AWG   26 AWG

### **Housing Features**

Housing Color	Orange
Housing Material	Polycarbonate

#### **Industry Standards**

UL Flammability Rating

UL 94V-0

## Mechanical Attachment

Mounting Type	SL Series Faceplate
Other	
Comment	With strain relief.

### **Packaging Features**

©2017 CommScope, Inc. All rights reserved. All trademarks identified by ® or ™ are registered trademarks, respectively, of CommScope. All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: May 19, 2017

## **Product Specifications**



1375191-5

Packaging Method	Poly Bag
Packaging Quantity	1

## **Product Availability**

Region

Asia | Australia/New Zealand | EMEA | Latin America | North America

## **Product Type Features**

Product Type	Modular Jack
Performance Category	Category 5e
Shielded	No
System	AMP NETCONNECT   SL 110 Series
Applies To	Panel
Cable Type	Unshielded Twisted Pair
Connector Style	Jack
Connector Type	Connector Assembly
Dust Cover	Without
Jack Type	RJ45

#### **Termination Features**

Termination Method to Wire/Cable	Insulation Displacement Crimp (IDC)
Termination Style	SL Termination Tool

#### **Regulatory Compliance/Certifications**

Agency RoHS 2011/65/EU Classification Compliant