

FST-D-HS | 1406152
Fiber Optic Splice Tray, 24 ports, 192-fiber

Product Classification

| | |
|-----------------------|-------------------|
| Product Type | Fiber splice tray |
| Regional Availability | North America |

Configuration Features

| | |
|------------------|---|
| Number of Fibers | 192 |
| Number of Ports | 24 |
| Splice Chip Type | Dual 24-fiber Single fiber heat shrink fusion |

Dimensions

| | |
|-------|---------------------|
| Depth | 127.00 mm 5.00 in |
|-------|---------------------|

Operation/Application

| | |
|--------------|--------------|
| For Use With | FEC Cabinets |
|--------------|--------------|

Packaging Features

| | |
|--------------------|---------|
| Packaging Method | Package |
| Packaging Quantity | 1 |

Product Type Features

| | |
|----------------|-------------|
| Accessory Type | Splice Tray |
|----------------|-------------|

Usage Conditions

| | |
|---------------------|----------------------------|
| Storage Temperature | -40 – 185 °F -40 – 85 °C |
|---------------------|----------------------------|

Regulatory Compliance/Certifications

| | |
|----------------------------------|------------------------------------|
| Agency RoHS 2011/65/EU | Classification Compliant |
|----------------------------------|------------------------------------|