B. Copper Systems

C. **Fiber Optic** Systems

D. Power over Ethernet

E. Zone Cabling

Wireless

G. **Outlets**

H. Media Distribution

I. **Physical** Infrastructure Management

J. Overhead & Underfloor Routing

Surface Raceway

L. Cabinets, Racks & Cable Management

Grounding 8 Bonding

N. Industrial

0. Labeling & Identification

P. Cable Management Accessories

> 0. Index

Opti-Core® Singlemode 9/125µm (OS1/OS2) Fiber Optic Patch Cords and Pigtails

- Available in riser (OFNR) or plenum (OFNP) flame ratings; part numbers listed are for OFNR (F9E10-10M1Y)
- For OFNP, place a P after the X in the part number and drop the Y (F9PE10-10M1)
- Pass all TIA/EIA-568-B.3 performance requirements
- · LC and SC connector housing and boot colors follow TIA/EIA-568-C.3 suggested color identification scheme
- 100% factory inspected end face geometry in compliance with Telcordia GR-326-CORE, Issue 3

Part Number

- Typical insertion loss per connection: 0.25dB
- UPC polished (55dB minimum return loss)
- Factory terminated and 100% tested for insertion loss and return loss
- Insertion loss and return loss data recorded for every singlemode patch cord
- · Lifetime traceability of test data to a Q.C. number on each patch cord

Std. Std. Length Pkg. Ctn.

Qty. Qty.

(m)^

 Highest quality flame retardant fiber optic cable with tight-buffered coating on each optical fiber




F9E10-10M*Y



F9F10-10M*V



F9B10-NM*Y



F9D3-3M*Y




F9S3-3M*Y



F9B3-NM*Y



F9D2-2M*Y



F9S2-2M*Y



F9D6P-6PM*Y

F9D6J-NM1Y

F9E10-10M1Y	LC to LC singlemode duplex patch cord, 1.6mm jacketed cable (one duplex LC connector on each end) – 9/125µm.	1	1	10
LC to LC - OS1	/OS2 Singlemode Simplex Patch Cords – 1.6mm Jacks	eted Cal	ole	
F9F10-10M1Y	LC to LC singlemode simplex patch cord, 1.6mm jacketed cable (one LC connector on each end) – 9/125µm.	1	1	10
LC to Pigtail – (OS1/OS2 Singlemode Simplex Pigtails – 900µm Buffer	ed Fiber	•	
F9B10-NM1Y	to pigtail singlemode simplex pigtail, 900µm buffered fiber 1 e LC connector on one end and open on the other d) – 9/125µm.		1	10
SC to SC - OS1	/OS2 Singlemode Duplex Patch Cords – 3mm Jackete	d Cable		
F9D3-3M1Y	SC to SC singlemode duplex patch cord, 3mm jacketed cable (two SC connectors on each end) – 9/125µm.	1	1	10
SC to SC - OS1	/OS2 Singlemode Simplex Patch Cords – 3mm Jacket	ed Cable	е	
F9S3-3M1Y	SC to SC singlemode simplex patch cord, 3mm jacketed cable (one SC connector on each end) $-9/125\mu m$.		1	10
SC to Pigtail - 0	OS1/OS2 Singlemode Simplex Pigtails – 900µm Buffer	ed Fiber		
F9B3-NM1Y	SC to pigtail singlemode simplex pigtail, 900µm buffered fiber (one SC connector on one end and open on the other end) – 9/125µm.		1	10
ST to ST - OS1	/OS2 Singlemode Duplex Patch Cords – 3mm Jacketed	d Cable		
F9D2-2M1Y	ST to ST singlemode duplex patch cord, 3mm jacketed cable (two ST connectors on each end) – 9/125µm.	1	1	10
ST to ST - OS1	/OS2 Singlemode Simplex Patch Cords – 3mm Jackete	ed Cable	•	
F9S2-2M1Y	ST to ST singlemode simplex patch cord, 3mm jacketed cable (one ST connector on each end) – 9/125µm.		1	10
ST to Pigtail – 0	OS1/OS2 Singlemode Simplex Pigtails – 900µm Buffer	ed Fiber		
F9B2-NM1Y	ST to pigtail singlemode simplex pigtail, 900µm buffered fiber (one ST connector on one end and open on the other end) – 9/125µm.		1	10
FJ® Plug to FJ®	Plug - OS1/OS2 Singlemode Duplex Patch Cords - 3mi	m Jacke	ted C	able
F9D6P-6PM1Y	FJ® Plug to FJ® Plug singlemode duplex patch cord, 3mm jacketed cable (one FJ® Plug on each end) – 9/125µm.	1	1	10

Part Description

LC to LC - OS1/OS2 Singlemode Duplex Patch Cords - 1.6mm Jacketed Cable

^Additional lengths and availability: Patch cords are available in 1 - 10 meter lengths in 1 meter increments, and 15, 20, 25 and 30 meter lengths. Pigtails are available in 1, 2, and 3 meter lengths. To order lengths other than 1 meter, replace the 1 after the M (F9D3-3M1Y) with the desired length (F9D3-3M2Y for 2 meter length). The above lengths are stock items. For other lengths, contact Customer Service for actual lead time.

FJ® Jack Module to Pigtail - OS1/OS2 Singlemode Duplex Pigtails - 3mm Jacketed Cable

jacketed cable (one FJ® Jack Module on one end and open on

FJ® Jack Module to pigtail singlemode duplex pigtail, 3mm



the other end) $-9/125\mu m$.

10

Systems

Q. Index

Opti-Core® Singlemode 9/125µm (OS1/OS2) Fiber Optic Patch Cords and Pigtails (continued)




F9B6J-NM*Y



F9E3-10M*Y



F9F3-10M*Y



F9D2-3M*Y



F9S2-3M*Y

- podd	=1
100	

F9E6P-10M*Y

innat rever	1	1
-		
0000		P

F9D6P-3M*Y

Part Number	Part Description		Std. Pkg. Qty.	
FJ® Jack Module to Pigtail – OS1/OS2 Singlemode Duplex Pigtails – 900µm Buffered Fiber				oer
F9B6J-NM1Y	FJ [®] Jack Module to pigtail singlemode duplex pigtail, 900μm buffered fiber (one FJ [®] Jack Module on one end and open on the other end) – 9/125μm.	1	1	10
SC to LC - OS1	SC to LC – OS1/OS2 Singlemode Duplex Patch Cords – 1.6mm Jacketed Cable			
F9E3-10M1Y	SC to LC singlemode duplex patch cord, 1.6mm jacketed cable (two SC connectors on one end and one duplex LC connector on the other end) – 9/125µm.	1	1	10
SC to LC – OS1/OS2 Singlemode Simplex Patch Cords – 1.6mm Jacketed Cable				
F9F3-10M1Y	SC to LC singlemode simplex patch cord, 1.6mm jacketed cable (one SC connector on one end and one LC connector on the other end) – 9/125µm.	1	1	10
ST to SC – OS1/OS2 Singlemode Duplex Patch Cords – 3mm Jacketed Cable				
F9D2-3M1Y	ST to SC singlemode duplex patch cord, 3mm jacketed cable (two ST connectors on one end and two SC connectors on the other end) – 9/125µm.	1	1	10
ST to SC - OS1	/OS2 Singlemode Simplex Patch Cord – 3mm Jackete	d Cable		
F9S2-3M1Y	ST to SC singlemode simplex patch cord, 3mm jacketed cable (one ST connector on one end and one SC connector on the other end) – 9/125µm.	1	1	10
FJ® Plug to LC	- OS1/OS2 Singlemode Duplex Patch Cords - 1.6mm	Jacketed	l Cab	le
F9E6P-10M1Y	FJ® Plug to LC singlemode duplex patch cord, 1.6mm jacketed cable (one FJ® Plug on one end and one duplex LC connector on the other end) – 9/125μm.	1	1	10
FJ® Plug to SC – OS1/OS2 Singlemode Duplex Patch Cords – 3mm Jacketed Cable				
F9D6P-3M1Y	FJ® Plug to SC singlemode duplex patch cord, 3mm jacketed cable (one FJ® Plug on one end and two SC connectors on the other end) – 9/125μm.	1	1	10

^Additional lengths and availability: Patch cords are available in 1 - 10 meter lengths in 1 meter increments, and 15, 20, 25 and 30 meter lengths. Pigtails are available in 1, 2, and 3 meter lengths. To order lengths other than 1 meter, replace the 1 after the M (F9D3-3M1Y) with the desired length (F9D3-3M2Y for 2 meter length). The above lengths are stock items. For other lengths, contact Customer Service for actual lead time.

B. Copper Systems

C. Fiber Optic Systems

D. Power over Ethernet

E. Zone Cabling

F. Wireless

> G. Outlets

H. Media Distribution

I. Physical Infrastructure Management

J. Overhead & Underfloor Routing

K. Surface Raceway

Cabinets, Racks & Cable Management

M. Grounding & Bonding

N. Industrial

0. Labeling & Identification

P. Cable Management Accessories

> Q. Index

Cable Self-Laminating Labels for Opti-Core® Singlemode 9/125µm (OS1/OS2) Fiber Optic Patch Cords and Pigtails



Suggested Label Solutions for TIA/EIA-606-A Compliance					
Patch Cord Part Number	Laser/Ink Jet Desktop Printer Label	TDP43ME Thermal Transfer Desktop Printer Label	PanTher™ LS8E Hand-Held Printer Label	Cougar™ LS9 Hand-Held Printer Label	
All F9F parts	S100X160YAJ and NWSLC-2Y‡	S100X150VATY and NWSLC-2Y‡	S100X160VAC and NWSLC-2Y‡	T100X000CBC-BK and NWSLC-2Y	
All F9S and F9E parts	S100X160YAJ and NWSLC-3Y‡	S100X150VATY and NWSLC-3Y‡	S100X160VAC and NWSLC-3Y‡	T100X000CBC-BK and NWSLC-3Y	
All F9D parts	S100X220YAJ and NWSLC-7Y‡	S100X225VATY and NWSLC-7Y‡	S100X220VAC and NWSLC-7Y‡	T100X000CBC-BK and NWSLC-7Y	

For complete labeling solutions and product information, reference charts on pages O.1 – O.18 of SA-NCCB51. ‡For complete information on fiber optic cable identification solutions, reference page C.92 of SA-NCCB51.