


| | |
|--|--|
| Material | High Conductivity Seamless Copper Tube |
| Plating | Electro-Tin |
| Wire Size | 500 STR/FLEX |
| Wire Type | Stranded Copper: Class G, H, I, K, M, Locomotive |
| Wire Strip Length | 1-9/16 in. |
| Stud Size | 3/8 in. |
| UL Listed Wire Connector | Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts. |
| UL Temperature Rating | 90° C |
| C.S.A Certified Wire Connector | Yes |
| Panduit Color Code on Barrel | PINK |
| Panduit Die Index No. on Barrel | P99 |
| Alternate Industry Die Index No. () on Barrel | (L99) |

| | | | | | |  PANDUIT CORP. TINLEY PARK, ILLINOIS | |
|-----|------|------|------|---|-----|--|--|
| | | | | | | LCDXN500-38D-6 Copper Lug - Narrow Tongue, Two-Hole, Standard Flex Barrel | |
| 04 | 1/11 | JHNU | JHNU | REVISED OVERALL LENGTH: WAS 4.32 REVISED TONGUE THICKNESS: WAS .28 | | | |
| REV | DATE | BY | CHK | DESCRIPTION | ECN | SCALE N/A | DRAWING NO / CAD FILE LCDXN500-38D-CUST |