

# i.Net

## OUTDOOR PAGING SPEAKER

MODEL WPSPKR-15



### FUNCTION

The Outdoor Paging Speakers are compact two-way speaker systems designed for high efficiency, wide range, and high power input handling capability. These speaker systems can be installed in a manner ideal for the location and intended application.

### FEATURES AND CAPABILITIES

- + 90° horizontal x 90° vertical wide directivity high-frequency horn.
- + Supplied bracket permits mounting to a wall, ceiling, or an optional speaker stand.
- + Feature a waterproof design (IPX4 standard) for protection from any adverse effects of outdoor installations.

### SPEAKER MODEL DIMENSIONS/WEIGHT

- + 130 (w) x 202 (h) x 131 (d) mm
- + 2kg

### ENCLOSURE TYPE

- + Bass-reflex type

### MESH SPEAKER GRILL

- + Surface-treated steel plate, black, anti-rust paint

### WATER RESISTANCE

- + IPX4

### INPUT TERMINALS

- + Push in Terminals

### FREQUENCY RESPONSE

- + 85 – 20,000 Hz, -10 dB at installation in a semianechoic field

### DIRECTIVITY ANGLE

- + Horizontal: 90°, Vertical: 90°

### POWER HANDLING CAPACITY

- + 15W

### SPEAKERS

- + Woofer: 10 cm cone-type
- + Tweeter: balanced dome-type

### CROSSOVER FREQUENCY

- + 5 kHz

### OPERATING TEMPERATURE

- + -10 °C to +50 °C

### OUTPUT SOUND PRESSURE LEVEL

- + 87 dB (1 W, 1 m) at installation in a semianechoic field

### RATED IMPEDANCE

- + 670  $\Omega$  (15 W), 2 k $\Omega$  (5 W), 3.3 k $\Omega$  (3 W), 10 k $\Omega$  (1 W)

