

EDGE8® Housings 2 rack unit, holds up to 36 EDGE8® modules or panels

CORNING

Part Number: EDGE8-02U

EDGE8® solutions are high-density preterminated optical cabling solutions with optimized design for Base-8 fiber applications offering industry-leading connector density. With sufficient connector finger access, there is no need for additional tools enabling faster moves, adds, and changes (MACs).



Features and Benefits

Smaller footprint design with Base-8 components in housings

Greater flexibility with six open slots per tray, for easy deployment of EDGE8® modules and panels

Key identifiers

EDGE8® printed on housing for easy identification as a Base-8 component

Sliding drawer-style hardware with integrated cable routing guides and port identification

Optimized finger access to connectors combined with industry leading port density

Integrated strain-relief plate can rotate 90°

Allows for rear cable entry direction, as well as the traditional side cable entry

Removable top covers on the 1U and 2U housings

Provides easier access to modules and panels

Quick mounting system

Enables one-person installation and depth adjustment of the housing in the rack

EDGE8® Housings 2 rack unit, holds up to 36 EDGE8® modules or panels

CORNING

Specifications

Design - Adapter

Adapter Type	ST® compatible
--------------	----------------

Design

Housing Type	EDGE
--------------	------

Number of Panels per Housing	36
------------------------------	----

General Specifications

Mounting Type	Rack 19-in
---------------	------------

Product Type	Fiber Optic Hardware
--------------	----------------------

Application	Data Center
-------------	-------------

Dimensions

Height	88 mm
--------	-------

Width	432 mm
-------	--------

Depth	561 mm
-------	--------

Shipping Dimensions

Height	241 mm
--------	--------

Width	578 mm
-------	--------

Depth	667 mm
-------	--------

EDGE8® Housings 2 rack unit, holds up to 36 EDGE8® modules or panels

CORNING

Connector Specs

Housing Color	Silver
---------------	--------

Ordering Information

Shipping Weight	10.4 kg
-----------------	---------

Units per Delivery	1/1
--------------------	-----

Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---



Corning Optical Communications GmbH & Co. KG • Lelpziger Strasse 121 • 10117 Berlin, Germany
+00 800 2675 4641 • FAX: +49 30 5303 2335 • www.corning.com/opcomm/emea