| THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP. |  |    |  |                  |                |                |              |       |           |                |   |           |   |                     |                     |                             |         |
|--|--|----|--|------------------|----------------|----------------|--------------|-------|-----------|----------------|---|-----------|---|---------------------|---------------------|-----------------------------|---------|
| CUT-THRU FOR #10 TRUSS HEAD SCREW.   |  |    |  |                  |                |                |              |       |           |                |   |           |   |                     |                     |                             |         |
| .300 REF.—<br>TYP.   |  |    | B<br>B<br>B<br>C<br>C<br>C<br>C<br>C<br>SEE NOTE #3<br>C<br>C<br>C<br>C<br>C<br>C<br>C<br>C<br>C<br>C<br>C<br>C<br>C<br>C<br>C<br>C<br>C<br>C<br>C |                  |                |                |              |       |           |                |   |           |   |                     |                     |                             |         |
| PANDUIT BUNDLE DIA. A B C D F MIN. LOOP * CROSS  |  |    |  |                  |                |                |              |       |           |                |   |           |   |                     |                     |                             |         |
|  |  |    | PART NO.   | 1                |                | A<br>in (mr    | n) in (mr    | n) iı | (mm)      | in (mn         | n) ir   |           | TENSILE Ibs.  | CROSS<br>SECTION    | Â                   |                             |         |
|  |  |    | HLT2I  |                  | .25<br>(6.4)   | 1.91<br>(48.5) | .100<br>(2.5 |       |           | 1.50<br>38.1)  | 1.00<br>(25.4                                 |           | 8.0<br>(203)  | 40<br>(178)         | INTERMEDIATE        |                             |         |
|  |  |    | Η  | LT3I             | .25<br>(6.4)   | 3.18<br>(80.6) | .100<br>(2.5 |       | )<br>7) ( | 1.50<br>(38.1) | 1.00<br>(25.4                                 |           | 12.0<br>(305)   | 40<br>(178)         | INTERMEDIATE        |                             |         |
|  | NOTES:<br>1) SEE CURRENT PRICE SHEET FOR PART NUMBER SUFFIX DESIGNATION FOR PACKAGE SIZE AND PART COLOR.<br>* 2) MINIMUM 2" OVERLAP REQUIRED TO ACHIEVE LOOP TENSILE RATING.<br>3) A MATERIAL SLUG MAY BE PRESENT AFTER MANUFACTURING. THE SLUG MAY REMAIN IN<br>THE SLOT OR BE ON THE TIES<br>CAD FILENAME/LAYERS SS_26938_08 |    |  |                  |                |                |              |       |           |                |   |           |   |                     |                     |                             |         |
|  |  |    |  |                  |                |                |              |       |           |                |   |           |   |                     |                     |                             |         |
|  |  |    |  |                  |                |                |              |       |           |                |   |           | т т   | AK - TY ™           |                     | CABLE TIES                  |         |
|  |  |    |  |                  |                |                |              |       |           |                | TAK-TY ™ HOOK & LOOP CABLE TIES<br>HLT SERIES |           |   |                     |                     |                             |         |
| 08   | 1/7/20   |    | DWW  | C. ADDED NOTE #3 | 26938<br>26938 | 8              | ML           |       |           | DIMEN          | S OTHERWISE S                                 | NCES ARE: | UNLESS OTHERWISE SPECIFIED,<br>ALL DIMENSIONS ARE GIVEN |                     |                     |                             |         |
|  | 01/14/19   |    |  |                  |                |                |              |       | 7         | ML             |   |           | ( .X)<br>( .XX)<br>DRAWN BY                             | ±.125 ANG           | XX) ± .030<br>_ES ± | IN INCHES, THIRD ANGLE PROJ | ECTION. |
| 6  | 1/16/06  |    | REMOVED OVAL SLOT DIMENSION TO BE  |                  |                |                |              | 26938 | 6         |                |   |           |   | MAT'L:<br>BACK-TO-E | ACK HOOK AND LOOP   | DRAWING ND.                 | DWG     |
| 5  | 5/3/05   |    | CONSISTENT WITH OTHER CUSTOMER DRAWINGS  |                  |                |                |              | 26938 | 5         | JVL            |   |           | СНК ' D   |                     |                     |                             |         |
| REV  | DATE   | BY | СНК  | DE               |                | ECN -          | н            | CUST  | SUP       |                | HVF   | ,         |   |                     | SIZE                |                             |         |